

Product Specifications (AFP 2000-C)

Standard Capacity Carbon Impregnated Pleated Air Filter

General

All filters shall be medium efficiency, pleated type air filters, consisting of non-woven polyester media, impregnated with activated carbon, media support grid and two-piece enclosure frame.

Construction

The dual-stage filter media shall be comprised of synthetic fibers upstream, forming the particulate layer, laminated to a carbon impregnated gas phase layer, which shall maintain a uniform depth of 0.18", and shall be pleated into a wedge shaped "V" configuration.

A galvanized expanded steel support grid shall be bonded to the downstream side of the media to maintain the wedge shaped pleat configuration and to prevent media oscillation.

The two-piece enclosure frame, constructed of 26-28 point, high wet strength clay coated kraft board, shall include overlapping flaps and interlocking corners to provide optimum strength and support of the pleated element. The frame shall be bonded to the pleated element at all contact points, thus providing uniform pleat spacing, allowing for optimum airflow and preventing air bypass.

The filter shall have no less than 12.0 square feet of media area, based on nominal dimensions of 24"x24"x2", (10 pleats per linear foot).

Performance

The filter shall have a MERV rating, (Minimum Efficiency Reporting Value) of 8, when evaluated in accordance with ASHRAE Standard 52.2-1999.

The filter shall have an average dust spot efficiency of 30-35%, when evaluated in accordance with ASHRAE Standard 52.1-1992.

The initial resistance to airflow, when tested at 500 fpm, shall not exceed 0.35" wg.

The filter shall be classified by Underwriters Laboratories as UL II.



GLOBAL FILTER SOURCE

6212-A Westgate Road, Raleigh, NC 27617

Phone: 919-571-4945

Website: www.global-filter.com